



(Description)	U	I	P1	M	n	P2	Eff
	(V)	(A)	(W)	(N.m)	(rpm)	(W)	(%)
(No_Load)	24.10	1.873	45.14	0.48	183.9	9.24	20.4
(Max_Eff)	24.04	6.437	154.8	4.96	138.3	71.82	46.3
(Max_Pout)	24.02	9.163	220.1	8.89	98.8	91.96	41.7
(Max_Torque)	24.02	9.163	220.1	8.89	98.8	91.96	41.7
(End)	24.02	9.163	220.1	8.89	98.8	91.96	41.7

(Voltage): 28V

(Power Rated): 180W

(Test Date): 2009.02.24

No:	U	I	P1	M	n	P2	EFF
	(V)	(A)	(W)	(N.m)	(rpm)	(W)	(%)
1	24.10	1.873	45.14	0.48	183.9	9.24	20.4
2	24.10	1.881	45.34	0.49	184.0	9.43	20.8
3	24.10	1.946	46.91	0.49	183.5	9.41	20.0
4	24.09	2.053	49.47	0.49	182.8	9.37	18.9
5	24.09	2.174	52.40	0.49	181.3	9.30	17.7
6	24.09	2.334	56.24	0.63	179.8	11.85	21.0
7	24.09	2.565	61.81	0.83	178.1	15.47	25.0
8	24.09	2.893	69.73	1.20	174.5	21.92	31.4
9	24.09	3.250	78.32	1.53	171.9	27.53	35.1
10	24.09	3.760	90.59	2.10	165.5	36.38	40.1
11	24.08	4.394	105.8	2.57	161.2	43.37	40.9
12	24.06	4.925	118.5	3.35	152.8	53.59	45.2
13	24.06	5.772	138.9	3.99	146.5	61.20	44.0
14	24.04	6.437	154.8	4.96	138.3	71.82	46.3
15	24.03	7.338	176.4	5.72	132.1	79.11	44.8
16	24.03	8.290	199.2	6.84	120.4	86.22	43.2
17	24.02	9.163	220.1	7.69	112.4	90.49	41.1
18	24.02	9.163	220.1	8.89	98.8	91.96	41.7